

Kinematics:  $v = v_o + at; \quad \Delta x = v_o t + (\frac{1}{2}) a t^2; \quad v^2 = v_o^2 + 2a(x - x_o)$

Kinetic Energy:  $K = \frac{1}{2} m v^2$

Coulomb's law:  $F = k \frac{|q_1||q_2|}{r^2} = \frac{1}{4\pi\epsilon_o} \frac{|q_1||q_2|}{r^2}$

Electric Field:  $\vec{E} = \frac{\vec{F}}{q_o} \quad E = \frac{1}{4\pi\epsilon_o} \frac{|q|}{r^2}$

Gauss's Law for E:  $\epsilon_o \Phi_E = q_{enc}$  where  $\Phi_E = \oint \vec{E} \cdot d\vec{A}$

Gauss's Law for B:  $\Phi_B = \oint \vec{B} \cdot d\vec{A} = 0$

Potential Difference:  $\Delta V = V_b - V_a = -\int_a^b \vec{E} \cdot d\vec{s}$

Potential (point charge):  $V = \frac{1}{4\pi\epsilon_o} \frac{q}{r}$

E from V:  $\vec{E} = -\frac{\partial V}{\partial x} \hat{i} - \frac{\partial V}{\partial y} \hat{j} - \frac{\partial V}{\partial z} \hat{k}$

Electric Potential Energy:  $U = \frac{1}{4\pi\epsilon_o} \frac{q_1 q_2}{r}$  (Pair of point charges)

Capacitors:  $q = CV$  &  $U_E = \frac{1}{2} CV^2 = \frac{q^2}{2C}$  (in general)

$$C = \frac{\epsilon_o A}{d} \quad (\text{parallel-plate capacitor}) \quad E = \frac{V}{d}$$

$$C_{eq} = \sum_{j=1}^n C_j \quad (\text{parallel}) \quad \frac{1}{C_{eq}} = \sum_{j=1}^n \frac{1}{C_j} \quad (\text{series})$$

Current:  $i = \frac{dq}{dt} = \int \vec{j} \cdot d\vec{A}$  where  $\vec{j} = (ne)\vec{v}_d$

Resistance:  $R = \frac{V}{i} \quad \rho = \frac{E}{j} \quad R = \rho \frac{l}{A}$

Power:  $P = iV = i^2 R = \frac{V^2}{R}$

Resistors:  $R_{eq} = \sum_{j=1}^n R_j$  (series)  $\frac{1}{R_{eq}} = \sum_{j=1}^n \frac{1}{R_j}$  (parallel)

Magnetic Force/Torque:  $\vec{F}_B = q\vec{v} \times \vec{B}$   $\vec{F}_B = i\vec{l} \times \vec{B}$   $\vec{\tau} = \vec{\mu} \times \vec{B}$   $|\vec{\mu}| = NiA$

Circulating Charge:  $qvB = \frac{mv^2}{r}$   $f = \frac{1}{T} = \frac{qB}{2\pi m}$

Biot-Savart Law:  $d\vec{B} = \frac{\mu_o}{4\pi} \frac{id\vec{l} \times \hat{r}}{r^2}$  or  $dB = \frac{\mu_o}{4\pi} \frac{idl \sin\theta}{r^2}$

Ampere's Law:  $\oint \vec{B} \cdot d\vec{l} = \mu_o (i_c + i_d)$  where  $i_d = \epsilon_o \frac{d\Phi_E}{dt}$

Solenoid:  $B = \mu_o in$   $L = \mu_o \pi n^2 R^2 l$   $n = N/l$

Faraday's Law:  $\epsilon = \oint \vec{E} \cdot d\vec{s} = -N \frac{d\Phi_B}{dt}$   $\Phi_B = \int \vec{B} \cdot d\vec{A}$   $\epsilon = vBL$

Inductors:  $L = \frac{N\Phi_B}{i}$   $\epsilon_L = -L \frac{di}{dt}$   $U_B = \frac{1}{2} Li^2$   $u_B = \frac{B^2}{2\mu_o}$

RC Circuits:

Charging Capacitor:  $q = C\epsilon(1 - e^{-t/RC})$   $i = \left(\frac{\epsilon}{R}\right)e^{-t/RC}$

Discharging Capacitor:  $q = q_o e^{-t/RC}$   $i = -\left(\frac{q_o}{RC}\right)e^{-t/RC}$

RL Circuits:  $i = \frac{\epsilon}{R} \left(1 - e^{-(R/L)t}\right)$  or  $i = I_o e^{-(R/L)t}$

LC Circuits:  $\omega = 2\pi f = \frac{2\pi}{T} = \frac{1}{\sqrt{LC}}$   $q = Q \cos \omega t$

Constants:  $c = 3.00 \times 10^8$  m/s (speed of light)  $k = 1/4\pi\epsilon_o = 8.99 \times 10^9$  N · m<sup>2</sup>/C<sup>2</sup>  
 $\epsilon_o = 8.85 \times 10^{-12}$  C<sup>2</sup>/N · m<sup>2</sup>  $m_e = 9.11 \times 10^{-31}$  kg (electron mass)  
 $m_p = 1.67 \times 10^{-27}$  kg (proton mass)  $e = 1.6 \times 10^{-19}$  C (charge on electron)  
 $\mu_o = 4\pi \times 10^{-7}$  T · m/A  $g = 9.81$  m/s<sup>2</sup>

Conversions: 1 MΩ = 10<sup>6</sup> Ω    1 gram = 10<sup>-3</sup> kg    1 mT = 10<sup>-3</sup> T    1 kV = 1000 V  
 1 m = 10<sup>2</sup> cm = 10<sup>3</sup> mm = 10<sup>6</sup> μm = 10<sup>9</sup> nm    1 eV = 1.6 × 10<sup>-19</sup> J

Geometry:  $S$  (cylinder) =  $2\pi rL + 2\pi r^2$      $S$  (sphere) =  $4\pi r^2$      $A$  (circle) =  $\pi r^2$   
 $V$  (cylinder) =  $\pi r^2 L$      $V$  (sphere) =  $(4/3)\pi r^3$      $C$  (circle) =  $2\pi r$

Calculus:  $\frac{d}{dx} \ln x = x^{-1}$      $\int \frac{dx}{x} = \ln x$      $\int x^n dx = x^{n+1}/n+1$      $\frac{d}{dx} e^u = e^u \frac{du}{dx}$